







慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



P.C.B. LAYOUT



UL/CUL 技术参数					
UL/CUL Technical Data					
等 级	Use Group		B	C	D
额定电压	Rated Voltage	[V]	150	—	—
额定电流	Rated Current	[A]	10	—	—
接线范围	Wire Range		/		
单/多芯线	Solid/Stranded	[AWG]			
耐电压	Withstanding Voltage		1300V/1Min		
IEC 技术参数			IEC 61984		
IEC Technical Data					
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage	[V]	80	125	250
额定电流	Rated Current	[A]	10	10	10
额定冲击电压	Impulse withstand voltage	[KV]	2.5	2.5	2.5
导线截面积	Conductor cross section		/		
硬质/柔性导线	Solid/ flexible	[mm²]			
材 料			Material		
绝缘材料	Insulation Material		LCP		
阻燃等级	Imflamability		UL94V-0		
导体材料	Contact Material		铜合金 Copper alloy		
导体镀层	Contactive Coating		镀锡 Sn Plated		
一般参数			Other Data		
间距	Pitch	[mm]	3.5		
极数	Poles	[P]	2*02~2*24		
剥线长度	Stripping Length	[mm]	/		
螺丝	Screw		/		
扭矩	Torque(Max)	[N.m]	/		
工作温度	Operating temperature	[°C]	-40~130		

linear dimension(Tolerances Standard GB/T 14486-2008)



<i>variable range</i>	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
<i>tolerance</i>	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	3:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	V0
						名称 / TITLE	WJ15EDGRHS-THR-3.5-2*XP-1YY-00A	