




慈溪市万捷电子有限公司

CIXI WANJIE ELECTRONIC CO., LTD

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	over 250 to 500	over 500 to 1000
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

UL/CUL 技术参数		UL/CUL Technical Data					
等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	-	300			
额定电流	Rated Current [A]	10	-	10			
接线范围	Wire Range	28-12					
单/多芯线	Solid/Stranded [AWG]						
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数					IEC61984		
IEC Technical Data							
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	320	320	630			
额定电流	Rated Current [A]	12	12	12			
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0			
导线截面积	Conductor cross section	0.2-2.5					
硬质/柔性导线	Solid/ flexible [mm²]						
材 料 Material							
绝缘材料	Insulation Material	PA66					
阻燃等级	Imflamability	UL94V-0					
导体材料	Contact Material	铜合金 Copper alloy					
导体表面镀层	Contactive Coating	镀锡 Sn Plated					
一般参数 Other Data							
间距 Pitch /极数 Poles	[mm] / [P]	5.0 / 02~24					
剥线长度	Stripping Length [mm]	7~8					
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]	-					
工作温度	Operating temperature [°C]	-40~105					
焊锡温度	Soldering temperature	-					
引针尺寸	Pin Dimensions [mm]	-					
PCB板孔径	PCB Hole Diameter [mm]	-					

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	2:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	V0
						名称 / TITLE	WJ2EDGKDRN-5.0-XXP-1YY-00A	



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD